

# A6500-TP - Temperature / Process Card

The A6500-TP Temperature Process Card is a component of the CSI 6500-ATG Machine Protection System. The card is equipped with 4 measuring channels for temperature measurements with thermocouples or resistance temperature detectors (RTDs) and for measurements of process signals 0 - 1 V, 0 - 10 V or 0/4 - 20 mA standard signals. Besides this, the card contains 2 digital inputs and 6 digital outputs. The measured signals are transmitted through the internal RS 485 bus to the A6500-CC Com Card and converted to Modbus RTU and Modbus TCP/IP protocols for further transmission to host computers or analysis systems. In addition, the Com Card provides the communication through the USB socket at the face plate for the connection to PC/laptop for the configuration of protection cards and for visualization of measuring results. Apart from that, the measuring results can be output through analog outputs 0/4 - 20 mA. These outputs have a common ground and are electrically isolated from system supply. The operation of the A6500-TP Temperature Process Card is performed in the A6500-SR System Rack, which also provides connection of supply voltages and signals. The A6500-TP Temperature Process Card provides the following functions:

- Temperature measurement with RTDs
- Temperature measurement with thermocouples with internal and external cold junction compensation
- Measurement of standard process signals 0 - 1 V, 0 - 10 V or 0/4 - 20 mA
- Acquisition of digital signals with two digital inputs
- Output of analog values for each measuring channel through 4 current outputs 0/4 - 20 mA
- Output of alarms through 6 digital outputs, the assignment to the measuring channels can be configured in any way

## Signal Inputs

Number of Inputs	Four (Up to Eight in Temperature Mode) - independently configurable for different temperature sensors or process signal inputs, nonreactive, short circuit proof.
Input Resolution	24 bit ADC
Isolation	The four inputs are galvanically isolated against each other based on levels of IEC 60204-1, respectively IEC 61131-2

## Voltage Process Inputs

Range	0 to 10 V
Accuracy	±1% of full scale
Impedance	>100 kΩ
Temperature Drift	±0.5% of full scale within operating temperature range of -20°C to +70°C



- Two-channel, 3U size, 1-slot plug-in module decreases cabinet space requirements in half from traditional four-channel 6U size cards.
- API 670 compliant, hot-swappable module.
- Self-checking facilities include monitoring hardware, power input, hardware temperature, sensor, and cable.
- Use with 2,3 or wire RTD's, thermocouples, or analog process input signals.



**Current Process Inputs**

Range	0/4 to 20 mA
Accuracy	± 1% of full scale
Impedance	<200 Ω
Temperature Drift	±0.5% of full scale within operating temperature range of -20°C to +70°C

**RTD Sensor Inputs**

Type	Pt100 (α =0.00385) Ni100 (α =0.00618) Ni120 (α =0.00672) Cu10 (α =0.00427)
Technology	2-, 3-, and 4-wire (Cu10 is not applicable in 2-wire technology)
Accuracy	± 1 K
Excitation Current	500 μA
Cable Resistance	<120 Ω per wire and if ex-application, including possible safety barrier impedance
Temperature Drift	± 1 K within operating temperature range of -20°C to +70°C

**Thermocouple Inputs**

Type	E, J, K, T, N
Accuracy	± 1 K
Cold Junction Compensation	exterior use RTD sensor input for cold junction compensation (CJC)
Capacity	<10 μF including sensor cable
Temperature Drift	± 1 K within operating temperature range of -20°C to +70°C

Environmental, General	
Protection Class	IP20, IEC 60529
Operating Temperature	-20°C to +70°C (-4°F to 158°F)
Storage Temperature	-40°C to +85°C (-40°F to 185°F)
Relative Humidity	5 to 95%, non-condensing
Vibration	IEC 60068-2-6 0.15mm, 10 – 55Hz 20m/s <sup>2</sup> , 55 – 150Hz
Shock	150 m/s <sup>2</sup> 4000 shocks per axis
EMR Resistance	EN50081-1 / EN50082-2
Power Consumption	Max. 5W
Configuration	Password protected
Rack Slot	3RU/6HP
Board Dimensions	PCB/EURO card format according to DIN 41494, 100 x 160mm (3.937 x 6.300in)
Weight	app 200g exclusive packaging

Compliance and Certifications	
CE	EMC – EN61326-1
	2014/30/EU
	2014/34/EU
	2011/65/EU
ATEX	EN 60079-0:2012
	EN 60079-15:2010
IEC-Ex	IEC 60079-0:2011; Edition: 6.0
	IEC 60079-15:2010; Edition: 4
CSA	CAN/CSA-C22.2 NO. 0-10
	CAN/CSA-C22.2 NO. 61010-1-12
	CAN/CSA-C22.2 NO. 60079-0:15
	CAN/CSA-C22.2 NO. 60079-15:12
	IEC 60529:2013 + COR2:2015
	UL 61010-1:12
	UL 60079-0:13
UL 60079-15:13	
Marine	DNV GL rules for classification – Ships and offshore units

## Hazardous Area Approvals

### Non-sparking nA in combination with nC

ATEX	II 3G – Ex nA nC IIC Gc, $-20^{\circ}\text{C} \leq T_s \leq 70^{\circ}\text{C}$ (with $T_s \leq 70^{\circ}\text{C}$ the requirements for temperature class T4 are met)
IEC-Ex	II 3G – Ex nA nC IIC Gc, $-20^{\circ}\text{C} \leq T_s \leq 70^{\circ}\text{C}$ (with $T_s \leq 70^{\circ}\text{C}$ the requirements for temperature class T4 are met)
CSA	Class I Division 2, Groups A, B, C, D, T4 Class 1, Zone 2 Ex / AEx nA nC IIC T4 Gc (the ambient temperature within the end use enclosure shall not exceed $55^{\circ}\text{C}$ )

## Ordering Information

Model Number	Product Description
A6500-TP	A6500-TP – TEMPERATURE / PROCESS CARD

©2016, Emerson Process Management. All rights reserved.

The Emerson logo is a trademark and service mark of Emerson Electric Co. Machinery Health is a mark of one of the Emerson Process Management family of companies. All other marks are the property of their respective owners.

The contents of this publication are presented for informational purposes only, and while every effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, expressed or implied, regarding the products or services described herein or their use of applicability. All sales are governed by our terms and conditions, which are available on request. We reserve the right to modify or improve the designs or specifications of our products at any time without notice.

**Emerson Process Management  
Reliability Solutions**  
835 Innovation Drive  
Knoxville, TN 37932 USA  
T 1(865) 675-2400  
[www.emersonprocess.com/csi](http://www.emersonprocess.com/csi)